PUMPS

SUZZARABLUE PUMPS

EN. The careful analysis of the market and the experience of handling aggressive fluid, such as AdBlue®, leads PIUSI to develop a new type of diaphragm pump equipped with electric motor without any dynamic seals. This solution provides a reliable industrial pump together with self priming capabilities.

ES. *Un minucioso estudio del mercado y la experiencia en manejar liquidos agresivos, tal como AdBlue®, han empujado PIUSI en desarrolar un nuevo tipo de bomba a membrana equipado con motor electrico sin estanquidad dinamica. Esta solucion permite de obtener una bomba industrial con una mayor fiabilidad y autocebante.*

RU. Благодаря внимательному анализу рынка и опыту, полученному в области перекачивания агрессивных жидкостей, таких как AdBlue®, компания PIUSI разработала новый тип мембранного насоса, оснащенного электродвигателем без динамических уплотнений. Это решение позволяет создать надежный промышленный насос с возможностью самозаливки.

PERFORMANCE

SUZZARABLUE AC PUMP
Technical features:
- Voltage 230/50 V
- Hose tail connection 3/4"
- Absence of dinamic seals
- ON/OFF switch
- 2 m cable with socket
- Duty cycle 20 min

SUZZARABLUE DC PUMP
Technical features:
- Voltage 12 / 24 V
- Hose tail connection 3/4"
- Absence of dinamic seals
- ON/OFF switch
- 2 m cable with clamps
- handle availble
- Duty cycle 20 min

SUZZARABLUE AC PUMP
Propriedad:
- 230/50 V voltaje
- Conexion 3/4"
- Sin estanquidad dinamica
- ON/OFF interruptor
- 2 m de cable con enchufe
- Ciclo de trabajo de 20 min

SUZZARABLUE DC PUMP
Propriedad:
- 12 / 24 V voltaje
- Conexion 3/4"
- Sin estanquidad dinamica
- ON/OFF interruptor
- 2 m de cable con pinzas
- Ciclo de trabajo de 20 min

SUZZARABLUE AC PUMP
Технические характеристики:
- Напряжение 230 В / 50 Гц
- Соединение для штуцера 3/4"
- Отсутствие динамических уплотнений
- Выключатель ВКЛ/ВЫКЛ
- Кабель 2 м со штепселем
- Рабочий цикл 20 мин.

SUZZARABLUE DC PUMP
Технические характеристики:
- Напряжение 12/24 В
- Соединение для штуцера 3/4"
- Отсутствие динамических уплотнений
- Выключатель ВКЛ/ВЫКЛ
- Кабель 2 м с зажимами
- Предлагается модель с ручкой
- Рабочий цикл 20 мин.

PRODUCTS' RANGE WEIGHT AND PACKAGING

Code	Weight		Packaging		N. Boxes/ Europallet	
	kg	lbs	mm	pcs/ box	✈	🚢
F00203090	7	15,4	350x180x280	1	60	84
F00203100	7	15,4	350x180x280	1	60	84
F00204080	3,6	7,9	350x180x280	1	60	84
F00204090	3,6	7,9	350x180x280	1	60	84

Flow-rate
up to
36 l/min
(up to 9,2 gpm)

PIUSI®

SUZZARABLUE
AC PUMP

SUZZARABLUE
DC PUMP

FEATURES

On/off switch

ON REQUEST

Kit handle

Code R16175010

PRODUCTS' RANGE TECHNICAL DATA

Code	Description	Fluids type	Flow-rate l/min	Flow-rate gpm	Voltage AC V./Hz DC Volt	Voltage rpm	Voltage Power Watt	Voltage Amp. max.	Cables mod.	Inlet - Outlet BSP	On/Off switch
F00203090	SuzzaraBlue AC pump 230/50	U	34	9	230/50	1450	400	1,95	YES	3/4"	YES
F00203100	SuzzaraBlue AC pump 120/60	U	34	9	120/60	1400	400	1,95	YES	3/4"	YES
F00204080	SuzzaraBlue DC pump 12V	U	36	9,2	12	2800	260	22	YES	3/4"	YES
F00204090	SuzzaraBlue DC pump 24V	U	36	9,2	24	2800	310	13	YES	3/4"	YES

OPW market

Дистрибутор:
България, София 1528, ул."Поручик Неделчо Бончев" 3, ет.5
+359 2 973 27 67, +359 2 973 2370; office_bg@opwmarket.com